

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A steering apparatus for controlling left and right drive wheels of a vehicle, comprising:

a driving force control section to control left and right driving forces of the left and right drive wheels individually in accordance with a running condition of the vehicle;

a power assistance device to add a steering assistance force to a driver's steering input force input to a steering input device;

a steering mechanism to link the left and right drive wheels with the steering input device so that the left and right drive wheels are turned in accordance with the driver's steering input force and the steering assistance force added thereto;

a steering reaction force calculating section to calculate a steering reaction force acting on the steering input device in accordance with a difference between the left and right driving forces; and

a steering force correcting section to correct the steering assistance force so as to compensate the steering reaction force by varying the steering assistance force in accordance with a turning direction of the vehicle,

wherein the steering force correcting section is configured to decrease the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to improve a yawing response of the vehicle, and to increase the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to restrain the yawing response of the vehicle.

2. (Currently Amended) A steering apparatus for controlling left and right drive wheels of a vehicle, comprising:

a driving force control section to control left and right driving forces of the left and right drive wheels individually in accordance with a running condition of the vehicle;

a power assistance device to add a steering assistance force to a driver's steering input force input to a steering input device;

a steering mechanism to link the left and right drive wheels with the steering input device so that the left and right drive wheels are turned in accordance with the driver's steering input force and the steering assistance force added thereto;

a steering reaction force calculating section to calculate a steering reaction force acting on the steering input device in accordance with a difference between the left and right driving forces; and

a steering force correcting section to correct the steering assistance force so as to compensate the steering reaction force,

wherein the steering force correcting section decreases the steering assistance force when the driving force control section increases the driving force of an outer drive wheel of the drive wheels outside of a turning radius of the vehicle, and

wherein the steering force correcting section is configured to decrease the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to improve a yawing response of the vehicle, and to increase the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to restrain the yawing response of the vehicle.

3. (Currently Amended) A steering apparatus for controlling left and right drive wheels of a vehicle, comprising:

a driving force control section to control left and right driving forces of the left and right drive wheels individually in accordance with a running condition of the vehicle;

a power assistance device to add a steering assistance force to a driver's steering input force input to a steering input device;

a steering mechanism to link the left and right drive wheels with the steering input device so that the left and right drive wheels are turned in accordance with the driver's steering input force and the steering assistance force added thereto;

a steering reaction force calculating section to calculate a steering reaction force acting on the steering input device in accordance with a difference between the left and right driving forces; and

a steering force correcting section to correct the steering assistance force so as to compensate the steering reaction force,

wherein the steering force correcting section increases the steering assistance force when the driving force control section decreases the driving force of an outer drive wheel of the drive wheels outside of a turning radius of the vehicle, and

wherein the steering force correcting section is configured to decrease the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to improve a yawing response of the vehicle, and to increase the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to restrain the yawing response of the vehicle.

4. (Currently Amended) A steering apparatus for controlling left and right drive wheels of a vehicle, comprising:

a driving force control section to control left and right driving forces of the left and right drive wheels individually in accordance with a running condition of the vehicle;

a power assistance device to add a steering assistance force to a driver's steering input force input to a steering input device;

a steering mechanism to link the left and right drive wheels with the steering input device so that the left and right drive wheels are turned in accordance with the driver's steering input force and the steering assistance force added thereto;

a steering reaction force calculating section to calculate a steering reaction force acting on the steering input device in accordance with a difference between the left and right driving forces; and

a steering force correcting section to correct the steering assistance force so as to compensate the steering reaction force,

wherein the steering force correcting section increases the steering assistance force when the driving force control section increases the driving force of an inner drive wheel of the drive wheels inside of a turning radius of the vehicle, and

wherein the steering force correcting section is configured to decrease the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to improve a yawing response of the vehicle, and to increase the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to restrain the yawing response of the vehicle.

5. (Currently Amended) A steering apparatus for controlling left and right drive wheels of a vehicle, comprising:

a driving force control section to control left and right driving forces of the left and right drive wheels individually in accordance with a running condition of the vehicle;

a power assistance device to add a steering assistance force to a driver's steering input force input to a steering input device;

a steering mechanism to link the left and right drive wheels with the steering input device so that the left and right drive wheels are turned in accordance with the driver's steering input force and the steering assistance force added thereto;

a steering reaction force calculating section to calculate a steering reaction force acting on the steering input device in accordance with a difference between the left and right driving forces; and

a steering force correcting section to correct the steering assistance force so as to compensate the steering reaction force,

wherein the steering force correcting section decreases the steering assistance force when the driving force control section decreases the driving force of an inner drive wheel of the drive wheels inside of a turning radius of the vehicle, and

wherein the steering force correcting section is configured to decrease the steering assistance force when the driving force control section controls the left and right driving forces of the left and right drive wheels in a direction to improve a yawing response of the vehicle, and to increase the steering assistance force when the driving

force control section controls the left and right driving forces of the left and right drive wheels in a direction to restrain the yawing response of the vehicle.

6. (Original) The steering apparatus as claimed in Claim 1, wherein the steering force correcting section corrects a magnitude of the steering assistance force so as to compensate the steering reaction force when the driving force control section corrects a magnitude of the driving force of one of the left and right drive wheels when the vehicle is running substantially straight.

7. (Original) The steering apparatus as claimed in Claim 1, wherein the steering force correcting section corrects a magnitude of the steering assistance force so as to compensate the steering reaction force when the driving force control section corrects a magnitude of the driving force of at least one of the left and right drive wheels in accordance with a running environment of the vehicle.

8. (Currently Amended) A steering process for controlling left and right steerable drive wheels of a vehicle, comprising:

controlling left and right driving forces of the left and right steerable drive wheels individually in accordance with a running condition of the vehicle,

examining a difference between the left and right driving forces individually controlled for the left and right steerable drive wheels turned in accordance with a driver's steering input force input to a steering input device and a steering assistance force added to the driver's steering input force; **and**

calculating a steering reaction force acting on the steering input device in accordance with a difference between the left and right driving forces;

varying the steering assistance force so as to compensate ~~[[a]]~~ the steering reaction force acting on the steering input device in accordance with the difference between the left and right driving forces when the driving force of one of an outer drive wheel of the steerable drive wheels outside of a turning radius of the vehicle~~[[,]]~~ and an inner drive wheel of the steerable drive wheels inside of the turning radius of the vehicle is varied; **and**

decreasing the steering assistance force when the steering assistance force is varied so that the left and right driving forces of the left and right steerable drive wheels are controlled in a direction to improve a yawing response of the vehicle, and increasing the steering assistance force when the steering assistance force is varied so that the left and right steerable driving forces of the left and right drive wheels are controlled in a direction to restrain the yawing response of the vehicle.

9. (Currently Amended) A steering apparatus for controlling left and right steerable drive wheels of a vehicle, comprising:

means for controlling left and right driving forces of the left and right drive wheels individually in accordance with a running condition of the vehicle;

means for calculating a steering reaction force caused in a steering input device by a left and right driving force difference between the left and right driving forces; and

means for varying a steering assistance force so as to compensate the steering reaction force,

wherein the means for varying the steering assistance force is configured to decrease the steering assistance force when the means for controlling left and right driving forces controls the left and right driving forces of the left and right drive wheels in a direction to improve a yawing response of the vehicle, and to increase the steering assistance force when the means for controlling left and right driving forces controls the left and right driving forces of the left and right drive wheels in a direction to restrain the yawing response of the vehicle.

10. (Previously Presented) The steering apparatus as claimed in Claim 1, wherein the driving force control section includes a left wheel motor to drive the left drive wheel to drive the vehicle, and a right wheel motor to drive the right drive wheel to drive the vehicle.

11. (Previously Presented) The steering apparatus as claimed in Claim 9, wherein the means for controlling left and right driving forces includes left wheel drive means

for driving the left drive wheel to drive the vehicle, and right wheel drive means for driving the right drive wheel to drive the vehicle.

12.-14. (Canceled)

15. (Previously Presented) The steering apparatus as claimed in Claim 1, wherein the steering reaction force calculating section is configured to calculate the steering reaction force in accordance with the difference between the left and right driving forces so that the steering reaction force is proportional to the difference between the left and right driving forces.

16. (Previously Presented) The steering apparatus as claimed in Claim 1, wherein the steering force correcting section is connected with the power assistance device, and configured to control the power assisting device to correct the steering assisting force of the power assistance device.

17. (Cancelled)